





Filter - B/V Filter



Storage temp: 15°C ~ 25°C Storage relative humidity: <85%





Date of Manufacture:



Contains: one (1) piece

Intended to reduce and filter the transmission of microbes and other particulate matter in breathing systems.

- *Flectrosatic media
- *High efficiency with low resistance filter
- *Filter efficiency: 99.99% (BFE), 99.9% (VFE)
- *Standard coaxial 22F for inlet port and 22M/15F for patient port

Caution:

- * Intended for use by qualified personnel trained.
- * For best performance, use within 3 years from the date of manufacture.
- * Store away from heat and light.
- * Do not sterilize.
- * The device is single use and must not be re-used. Reuse may cause cross infection and reduce product reliability and functionality.

Instruction of use:

- * Take the fitler out from package, make sure the filter inside is in good condition without damage.
- * Connect the filter to the tube or parts.
- * Make sure the connections are sealed and tight.
- * Start to use

Manufactured by HSINER Co.,Ltd.

312, Jhongshan Rd., Shengang Dist, Taichung City 429, Taiwan Tel: 886-4-25152480

Fax: 886-4-25152482 Email:sales@hsiner.com Web Site:http://www.hsiner.com

EC REP EU Representative mdi Europa GmbH Langenhagener Str. 71, D-30855 Langenhagen Tel: +49 511 3908 9530 Fax: +49 511 3908 9539 http://www.mdi-europa.com

AT0017053010 Rev.10 13/07/20